








# Pendulum Spreaders



Model PDC-400  
3 Point Hitch

- Category 1, three point hitch, 540 rpm PTO
- Corrosion proof poly hopper
- Pendulum style spreading mechanism
- Precise spreading rate adjustment
- Spreading widths from 20' to 45' with standard spout \*\*
- Spreading rates from 20 to 900 lbs. per acre
- Optional spreading spouts for narrow widths or banding



PDV series  
Large capacity models

- Category 1 & 2 three point hitch, 540 rpm PTO
- Corrosion proof molded plastic hopper
- Pendulum style spreading mechanism
- Precise spreading rate adjustment
- Spreading widths from 20' to 45' with standard spout
- Spreading rates from 20 to 900 lbs. per acre



## Specifications

Models	PDC-400C	PDV-500	PDV-600	PDHV-800
Capacity (lbs.)	925	1155	1450	2000
Capacity (cu. ft.)	13	17	20.5	32
Overall height	47"	36"	40"	40"
Overall width	46"	54"	54"	74"
Spreading width**	20' to 45'	20' to 45'	20' to 45'	20' to 45'
Weight (lbs.)	225	290	315	375



10784 Industrial Parkway  
Marysville, OH 43040  
www.forddistributing.com

Tel: 614-873-4620  
Fax: 614-873-8584  
Toll free: 888-222-8455

# FRONTLINE Spreaders



PL Series  
3 Point Hitch

- Category 1, three point hitch, 540 rpm PTO
- Corrosion proof poly hopper
- Stainless steel spreading disc with 4 steel vanes
- Side discharge gates with choice of center, right or left spreading pattern
- Spreading widths from 20' to 45' depending on material
- Spreading rates from 20 to 900 lbs. per acre
- Optional reinforced gearbox and chain agitator for winter salt and sand use
- Optional spreading width limiter

PTP Series  
Pull-type

- Pull-type spreader with ground wheel drive
- Corrosion proof poly hopper
- Stainless steel spreading disc with 4 steel vanes
- Side discharge gates with center, right or left spreading
- Oil bath gearbox with disengaging drive
- Clevis hitch for use behind ATV or small tractor
- Tires 16 x 6.5 –8 ply turf style
- Spreading widths from 20' to 45' depending on material
- Spreading rates from 20 to 900 lbs. per acre



## Specifications

Models	PL-180	PL-400	PL-500	PTP-180-P	PTP-300-P
Capacity (lbs.)	480	765	1000	480	765
Capacity (cu. ft.)	5.8	9.2	12.3	5.8	9.2
Overall height	36"	42"	45"	51"	51"
Spreading width	20' to 45'	20' to 45'	20' to 45'	20' to 45'	20' to 45'
Hopper width	36"	41"	44"	36"	41"
Weight (lbs.)	120	130	140	175	185



10784 Industrial Parkway  
Marysville, OH 43040  
www.forddistributing.com

Thomas Bros. Equipment Sales, Inc.  
41764 Red Arrow Hwy., Paw Paw, MI 49079  
269-657-3735 Fax:269-657-2110  
Toll Free 866-214-6135  
tbrofab@gmail.com

www.thomasbrosequipmentsales.com