



POST DRIVERS



*Professional - Grade
Power and Performance*

www.shavermfg.com

FARMERS AND FENCING CONTRACTORS WHO BUILD FENCES FOR A LIVING,

will tell you that you can't find a better post driver than a Shaver. Shaver's professional-grade post drivers are engineered for the most demanding jobs, from tough soil conditions to tricky side hills to having the ability to drive a wide variety of post types.

In fact, you won't find another company who has spent more time engineering the best post driver in the industry. How do we know? Because we invented and patented the world's first powered post driver more than a half-century ago.

While Shaver is the only choice for powerful, high performance post drivers, we give you a choice of drivers to fit your operation. Choose between skid steer loader-mounted drivers or tractor-mounted models. On tractor-mounted models, you have a choice between front or rear-mounted models. And, you can choose your model based on the pounding power you need and the types of posts you plan to install. Regardless of which model you choose, you can be assured that you'll get the quality that professionals have come to know Shaver for.

POWER

With models delivering up to 100,000 pounds of impact, Shaver post drivers can drive everything from steel posts, wood posts, even railroad ties into the ground.

SIMPLICITY

Shaver post drivers make it driving posts simple. Just load the driver and go. No digging, no pointing, no tamping and no setting.

SPEED

Shaver post drivers make quick work out of fence building chores, allowing you to drive a four or five inch post in as little as 10 to 15 seconds.

PILOT AUGER

The optional Shaver Pilot Auger Attachment makes post driving in the toughest soil conditions even easier. The unit's powerful 4 inch auger opens a pilot hole before driving the post. This new option reduces wear on the driver and significantly increases productivity by allowing the operator to drive posts more quickly. The unit is especially useful in tough, compacted soil conditions or when driving larger diameter posts (like railroad ties) and is available for both the HD-10 and HD-12 units.



"POSITIONER" HYDRAULIC EXTENSION UNIT

The optional "Positioner" lets you position the driver with pinpoint accuracy. A hydraulic swivel rotates the driver up to 155 degrees and extends 24 inches past the tire, making it much easier to position posts without the need to move the tractor. The unit is available for all Shaver drivers.

RELIABILITY

You can be sure that your post driver will pay for your investment in it long before it's done working for you.

SELF-CONTAINED POWER

Self-contained unit with its own hydraulic system eliminates dirt and foreign material in the operator's skid steer loader's hydraulic system.



Professional – Grade Power and Performance

QUICK-TACH

Reduce setup time with Shaver's Quick-Tach system. With the Quick-Tach bracket, you can hook up to any skid steer loader in no time.

COMMITMENT TO SAFETY

Shaver Manufacturing is committed to safety. That's why every Shaver post driver we build is engineered with your safety in mind:

- Offset controls let the operator stand safely to the side of the driver.
- Rubber guard shields the operator from impact and any flying debris.
- Safety arm securely positions posts in the driving ram.
- Standard stabilizer package provides greater stability during operation.



Offset controls allow the operator to stand safely to the side of the unit while posts are being driven.



A patented safety arm attachment holds the post in position, providing added safety for the operator.



The driver is mounted on a base plate that allows the unit to tilt in two directions, making it easy to drive posts straight—even in uneven terrain.

Tips for Operating Your Post Driver Safely

- Follow instructions on the driver's safety decals and read the owner's manual.
- Never stand in front of the driver. Always stand to one side of the post being driven.
- Always use the factory supplied safety arm to hold the post in position.
- Keep hands on the safety arm handle, never on top of the post.
- Keep the valve safety handle in place.
- Adjust the cylinder lock nut at the top of the cylinder before operating.
- Never use the maximum force of the driver until you are sure the post is being driven straight.
- Always consider the operating environment. Steep slopes can cause rollovers.
- Always check for underground pipelines and wires. Call utility companies for locations.
- Use caution when driving small diameter wood and steel posts.
- Use caution if you hit a rock while driving a post; the post can splinter and flying parts can cause injury. If the post fails to drive down after two or three strokes, move the post to another location.
- Do not try to drive posts in deeply frozen ground. Wait until the ground has thawed.
- Do not operate the post driver with the power unit unattended.
- Engage the road lock with pin when transporting or storing the driver.



POST DRIVERS

Professional – Grade Power and Performance



FEATURES AND SPECIFICATIONS	HD-8	HD-10	HD-12
Impact at Full Stroke	30,000 lbs.	71,500 lbs.	100,000 lbs.
Effective Weight of Spring-Powered Hammer	360 lbs.	725 lbs.	1,100 lbs.
Operating Distance Above Ground	53" – 126"	53" – 128"	53" – 128"
Max. Post Width	7 – 1/8"	8 3/4"	10 – 7/8"
Max. Post Length	10'	10'	10'
No. of Block Studs	4	8	8
No. of Nyrin Blocks	4	8	8
Tilt	Front-back/side-side	Front-back/side-side	Front-back/side-side
With Manual Base Plate	15 degrees / 15 degrees	15 degrees / 15 degrees	N/A
With Hydraulic Base Plate	15 degrees / 15 degrees	15 degrees / 15 degrees	20 degrees / 25 degrees
4 Inch Pilot Auger Attachment	N/A	optional	optional
Category I, II or III Assembly	Cat I & II	Cat II & III	Cat II & III
Mounting	front or rear or skid loader	front or rear or skid loader	rear or skid loader
Hydraulic Requirements	3 – 4 gpm / 1,500 psi	12 gpm / 1,500 psi	15 gpm / 2,000 psi
Approx. Shipping Weight With Hydraulic Base Plate	486 lbs.	714 lbs.	957 lbs.
With Manual Base Plate	438 lbs.	694 lbs.	N/A

THE POSITIONERS	SB-02	SB-12	SB-22
Collapsed Width	66"	66"	92"
Extended Width	90"	90"	116"
Height	37 1/2" – 55 1/2"	37 1/2"	37 1/2"
Weight	705 lbs.	680 lbs.	861 lbs.
Swivel	0 – 155 degrees	0 – 155 degrees	0 – 155 degrees

SELECTING THE RIGHT POST DRIVER

- Consider the size of your jobs, time available, labor costs and frequency of use.
- If you need a greater speed and more precise controls, consider a larger model with optional equipment.
- If your posts are less than 7 – inches in diameter and 7 – feet long, choose the HD – 8. If you have adverse ground (i.e. rocks or clay) you may need an HD – 10.
- If your posts are wider than 7 – inches in diameter, you'll need an HD – 10. Adverse ground conditions may require an HD – 12.
- Commercial fencing contractors will likely want the HD – 12 to meet varying requirements.

Shaver Manufacturing is a leading manufacturer of fencing equipment. We manufacture a complete lineup of post drivers, post hole diggers, stump grinders and log splitters. We're proud of the fact that our equipment is made in the Heartland of America – Graettinger, Iowa.

Shaver Manufacturing Company / PO Box 358 / Graettinger, Iowa, 51342
(712) 859-3293 / Fax: (712) 859-3294 / E-mail: sales@shavermfg.com

Thomas Bros. Equipment Sales, Inc.
 41764 Red Arrow Hwy.
 Paw Paw, MI 49079
 269-657-3735 Fax: 269-657-2110
 Toll Free 866-214-6135
 tbrofab@gmail.com
 www.thomasbrosequipmentsales.com





HD/8 Feature and Benefit

The HD/8 delivers 30,000 lbs of impact force at full stroke.

- The HD/8 will drive a 4"-5" post in 10 seconds or less in ideal conditions
- In ideal conditions the HD/8 can drive post up to 7.5".
- In most conditions the HD/8 will drive post in 10-20 seconds.

The HD/8 has only 8 moving parts.

- By minimizing moving parts fail points are reduced resulting in considerable savings in operating cost over other machines.
- Serviceable components are stocked and readily available at dealers, distributors, and warehouses' to get you back to work quickly reducing lost time.
- The simple straight forward design allows for repairs and maintenance to be done in the field by the user. This reduces repair and service cost over other machines.

The HD/8 tilts up to 15 degrees front to back and left to right.

- Allows the user to adjust the driver to terrain to maintain a straight fence line.
- Allows the user to adjust the driver between strikes, allowing the user to drive the post straight as it hits rocks and tough soil.
- Allows the user to apply pressure to a post that needs to be straightened as it is driven.

The HD/8 can mount on a Category I three point hitch.

- Allows the user to utilize smaller tractors to maneuver into less accessible areas.
- By utilizing a smaller tractor the user will incur less fuel cost than on a larger machine.
- The Cat I hitch provides opportunity to mate the driver with most tractors.

The HD/8 requires only 3-4 GPM to operate.

- Allows the use of the HD/8 on virtually any size tractor with auxiliary hydraulics.
- The HD/8 will have a diminutive effect on the host tractor hydraulics, causing no wear and tear while in use.
- The low hydraulic requirements give the user an opportunity to mount the driver on a very broad age range of tractors.

Overview:

The HD/8 is an occasional use, low maintenance, driver designed to give property owners the ability to drive 4"-5" post in most conditions on most terrain. It will save considerable time and money over operating other machines and methods of placing post.



HD/10 Feature and Benefit

The HD/10 delivers 71,500 lbs of impact force at full stroke.

- The HD/10 will drive a 6” post in 15 seconds or less in most conditions.
- In most conditions the HD/10 can drive post up to 8.75”.
- In most conditions the HD/10 will drive most post in 10-20 seconds.

The HD/10 has only 8 moving parts.

- By minimizing moving parts fail points are reduced resulting in considerable savings in operating cost over other machines.
- Serviceable components are stocked and readily available at dealers, distributors, and warehouses’ to get you back to work quickly reducing lost time.
- The simple straight forward design allows for repairs and maintenance to be done in the field by the user. This reduces repair and service cost over other machines.

The HD/10 tilts up to 15 degrees front to back and left to right.

- Allows the user to adjust the driver to terrain to maintain a straight fence line.
- Allows the user to adjust the driver between strikes, allowing the user to drive the post straight as it hits rocks and tough soil.
- Allows the user to apply pressure to a post that needs to be straightened as it is driven.

The HD/10 can mount on a Category II or III three point hitch.

- Allows the user to select the most appropriate tractor size for the job.
- By utilizing a smaller tractor the user will incur less fuel cost than on a larger machine.
- The Cat II or III hitch option provides the opportunity to mate the driver with most utility or row-crop tractors.

The HD/10 requires 12 GPM at only 1,500 psi to operate.

- Allows the use of the HD/10 on virtually any size utility or row-crop tractor with auxiliary hydraulics.
- The HD/10 will have little effect on the host tractor hydraulics, causing minimum wear and tear while in use.
- The hydraulic requirements give the user an opportunity to mount the driver on a very broad age range and size of tractors.

Overview:

The HD/10 is a regular use, low maintenance, driver designed to give property owners and contractors the ability to drive 6” post or larger in most conditions on most terrain. It will save considerable time and money over operating other machines and methods of placing post.



HD/10 Feature and Benefit

The HD/10 delivers 71,500 lbs of impact force at full stroke.

- The HD/10 will drive a 6” post in 15 seconds or less in most conditions.
- In most conditions the HD/10 can drive post up to 8.75”.
- In most conditions the HD/10 will drive most post in 10-20 seconds.

The HD/10 has only 8 moving parts.

- By minimizing moving parts fail points are reduced resulting in considerable savings in operating cost over other machines.
- Serviceable components are stocked and readily available at dealers, distributors, and warehouses’ to get you back to work quickly reducing lost time.
- The simple straight forward design allows for repairs and maintenance to be done in the field by the user. This reduces repair and service cost over other machines.

The HD/10 tilts up to 15 degrees front to back and left to right.

- Allows the user to adjust the driver to terrain to maintain a straight fence line.
- Allows the user to adjust the driver between strikes, allowing the user to drive the post straight as it hits rocks and tough soil.
- Allows the user to apply pressure to a post that needs to be straightened as it is driven.

The HD/10 can mount on a Category II or III three point hitch.

- Allows the user to select the most appropriate tractor size for the job.
- By utilizing a smaller tractor the user will incur less fuel cost than on a larger machine.
- The Cat II or III hitch option provides the opportunity to mate the driver with most utility or row-crop tractors.

The HD/10 requires 12 GPM at only 1,500 psi to operate.

- Allows the use of the HD/10 on virtually any size utility or row-crop tractor with auxiliary hydraulics.
- The HD/10 will have little effect on the host tractor hydraulics, causing minimum wear and tear while in use.
- The hydraulic requirements give the user an opportunity to mount the driver on a very broad age range and size of tractors.

Overview:

The HD/10 is a regular use, low maintenance, driver designed to give property owners and contractors the ability to drive 6” post or larger in most conditions on most terrain. It will save considerable time and money over operating other machines and methods of placing post.

GRAND SLAM

SPRINGLESS POST DRIVER

EVERYTHING YOU EXPECT from
a Shaver post driver *EXCEPT THE
SPRINGS, BLOCKS OR STUDS.*

Its new design delivers:



POWER

*Drive anything from steel and wood posts to
railroad ties. Up to 100,000 pounds of impact!*



SIMPLICITY

Just load the driver and go.



SPEED

Drive a four- or five-inch post in 10 to 15 seconds.



RELIABILITY

*Built to endure the toughest conditions.
Count on the Grand Slam to pay for itself.*



GRAND SLAM SPRINGLESS POST DRIVER

ASK ANY **FARMER OR FENCING CONTRACTOR** what the best post driver is, and they'll tell you, "**SHAVER.**" Perfect for any condition, from tough soil conditions to tricky side hills, our professional - grade post drivers are engineered for **YOUR MOST DEMANDING JOBS.**

FEATURES AND SPECIFICATIONS

Impact at Full Stroke	100,000 lbs.
Operating Distance Above Ground	53" - 128"
Max. Post Width	10 - 7/8"
Max. Post Length	10'
Tilt	Front - back / side - side
With Hydraulic Base Plate	20 degrees / 25 degrees
Category I, II or III Assembly	Cat. II & III
Mounting	Rear or skid loader
Hydraulic Requirements	15 gpm / 2,000 psi
Approx. Shipping Weight with Hydraulic Base	957 lbs.

THE POSITIONERS

SB-22	SB-22
Collapsed Width	92"
Extended Width	116"
Height	37 - 1/2"
Weight	861 lbs.
Swivel	0 - 155 degrees

AVAILABLE MODELS:

SKID STEER LOADER
mounted models

TRACTOR
mounted models
front - or rear - mounted
models



SELF-CONTAINED POWER

Eliminates dirt and foreign material in the operator's skid steer loader's hydraulic system to save you maintenance costs.

COMMITMENT TO SAFETY

Our commitment to safety shows through in every post driver we build.

Rubber guard shields the operator from impact and any flying debris.



Standard stabilizer package provides greater stability during operation.



Safety arm securely positions posts in the driving ram.



Offset controls let the operator stand safely to the side of the driver.



DISTRIBUTED BY:

Thomas Bros. Equipment Sales, Inc.
41764 Red Arrow Hwy.
Paw Paw, MI 49079
269-657-3735 Fax: 269-657-2110
Toll Free 866-214-6135
tbrofab@gmail.com
www.thomasbrosequipmentsales.com

Shaver Manufacturing is a leading manufacturer of fencing equipment. We manufacture a complete lineup of post drivers, post hole diggers, stump grinders and log splitters. We're proud of the fact that our equipment is made in the Heartland of America—Graettinger, Iowa.

Shaver Manufacturing Company

PO Box 358 / Graettinger, Iowa 51342
(712) 859-3293 / (712) 859-3294 fax / sales@shavermfg.com

